

GENERAL NOTES

- A. ALL WORK SHOWN IS NEW AND PROVIDED BY THE ELECTRICAL CONTRACTOR UNLESS OTHERWISE
- B. REMOVE OR RELOCATE ANY AND ALL EXISTING SERVICES, POLES, ETC., AS MAY BE REQUIRED TO ACCOMMODATE NEW CONSTRUCTION UNLESS OTHERWISE INDICATED.
- C. COORDINATE ALL INCOMING ELECTRICAL SERVICE WORK WITH THE ELECTRICAL UTILITY COMPANY. PAY ALL FEES AND OTHER COSTS NOT BORNE BY THE ELECTRICAL UTILITY COMPANY TO PROVIDE NEW ELECTRICAL SERVICES TO THE PROJECT BUILDINGS.
- D. COORDINATE ALL INCOMING TELEPHONE SERVICE WORK WITH THE LOCAL TELEPHONE UTILITY COMPANY. PAY ALL FEES AND OTHER COSTS NOT BORNE BY THE LOCAL TELEPHONE UTILITY COMPANY TO PROVIDE NEW TELEPHONE SERVICES TO THE PROJECT BUILDINGS.
- E. PROVIDE PULL STRINGS IN ALL UTILITY CONDUITS.
- F. ALL EXTERIOR CONDUITS SHALL BE INSTALLED BELOW THE FROST LINE. G. COORDINATE LOCATIONS OF ALL UNDERGROUND CONDUITS, HANDHOLES AND MANHOLES,
- H. PROVIDE ADDITIONAL HANDHOLES AND MANHOLES AS REQUIRED BY THE UTILITY COMPANIES. COORDIANTE REQUIREMENTS WITH UTILITY COMPANIES PRIOR TO BID. I. COORDINATECOORDINATE ALL ROUTING AND TERMINATION LOCATIONS WITH THE UTILITY COMPANIES

PLAN NOTES

1 DISCONNECT AND REMOVE EXISTING UTILITY METER COMPLETE.

UNDERGROUND DRAINS, SERVICES, STRUCTURES, AND PAVING.

- 2 EXISTING SECONDARIES. PROTECT EXISTING SERVICES. PROVIDE CONDUITS FROM TRANSFORMER SECONDARY TO 'P1' FOR CONDUCTORS. REFER TO ELECTRICAL ONE-LINE RISER DIAGRAM FOR ADDITIONAL INFORMATION.
- 4 UTILITY METER LOCATION. COORDINATE ALL REQUIREMENTS AND LOCATION WITH UTILITY. PROVIDE ADDITIONAL SUPPORT STRUCTURE AS REQUIRED AS REQUIRED BY THE UTILITY. REFER TO
- ELECTRICAL ONELINE RISER DIAGRAM FOR ADDITIONAL INFORMATION. 5 PROVIDE (2) 4" TELECOM SERVICE ENTRANCE CONDUITS FROM TELECOM BACKBOARD TO EXISTING
- TELECOM PEDESTAL. 6 EXISTING DUKE ENERGY SITE LIGHT TO BE RELOCATED BY UTILITY.
- 7 EXISTING DUKE ENERGY SITE LIGHT.
- 8 DUKE ENERGY TO PROVIDE SITE LIGHTING.
- 9 FUTURE ELECTRIC VEHICLE CHARGING STATION. PROVIDE QUAZITE BOX, CONDUIT AND BREAKER
- 10 GENERATOR. PROVIDE CONCRETE PAD PER MANUFACTURER'S REQUIREMENTS. REFER TO ELECTRICAL RISER DIAGRAM ON SHEET E701 FOR ADDITIONAL INFORMATION.
- 11 CIRCUIT CONNECTION TO BATTERY CHARGER. VERIFY LOCATION. 12 PROVIDE 2P-30A, 208V, NEMA 3R FUSIBLE DISCONNECT SWITCH FOR BLOCK HEATER. FUSE PER MANUFACTURERS RECOMMENDATIONS.

UTILITY CONTACT INFO FOR SITE LIGHTING: DUKE ENERGY

BRONSON GOSS BRONDON.GOSS@DUKE-ENERGY.COM (812)-374-3742

DELV DES GN

WINDROSE

WINDROSE FRANKLIN **CLINIC EXPANSION**

ARCHITECT

DELV Design 212 W 10th St, STE F125 Indianapolis, IN 46202 (317) 296-7400

MEP


Genesis Engineering Group 91 S Main St #200 Zionsville, IN 46077 (317) 927-8307

STRUCTURAL


JPS Consulting Engineers 9365 Counselors Row Indianapolis, IN 46240 (317) 617-4270

CIVIL

JPS Consulting Engineers 9365 Counselors Row Indianapolis, IN 46240 (317) 617-4270



1ST FLOOR KEY PLAN CONSTRUCTION DOCUMENTS



No.	Description	Date

CLIENT PROJ. #: N/A PROJECT #: 20-061 ISSUE DATE: 5/12/22 DRW: JAW | CHK: JAW

ELECTRICAL SITE PLAN

E100

