



SITE DIMENSION LEGEND	
A	NURSERY SOD
B	MULCHED TREE RINGS (SEE LANDSCAPE PLAN-SHEET 500)
C	STRAIGHT CONCRETE CURB (SEE DETAIL-SHEET 700)
D	4" CONCRETE SIDEWALK (SEE DETAIL-SHEET 700)
J	FULL DEPTH SAWCUT
K	TYPICAL ASPHALT PARKING LOT SECTION 165 LB/SYD HMA SURFACE TYPE B, ON 385 LB/SYD HMA INTERMEDIATE TYPE B, ON 8" COMPACTED AGGREGATE #53 BASE, ON GEGRID TYPE IB, ON SUBGRADE TREATMENT, TYPE III (SEE DETAIL-SHEET 700)
P	TYPICAL ASPHALT PATH SECTION 140 LB/SYD HMA SURFACE TYPE A, ON 220 LB/SYD HMA INTERMEDIATE TYPE A, ON 8" COMPACTED AGGREGATE #53 BASE, ON GEGRID TYPE IB, ON SUBGRADE TREATMENT, TYPE III (SEE DETAIL-SHEET 700)
W	CONCRETE WHEEL STOP (SEE DETAIL-SHEET 700)
1	TRANSVERSE MARKING, THERMOPLASTIC, SOLID WHITE, 4 INCHES, PARKING
2	TRANSVERSE MARKING, THERMOPLASTIC, SOLID BLUE, 4 INCHES, PARKING
3	TRANSVERSE MARKING, THERMOPLASTIC, CROSSHATCH LINE, SOLID BLUE, 4 INCHES
4	PAVEMENT MESSAGE MARKING, THERMOPLASTIC, SOLID BLUE, HANDICAP SYMBOL
5	TRANSVERSE MARKING, THERMOPLASTIC, SOLID WHITE, STOP BAR, 24 INCHES

SITE DIMENSION NOTES	
1.	SIGNAGE AND LIGHTING SHALL CONFORM TO CITY OF FRANKLIN STANDARDS. CONTRACTOR SHALL CONFIRM LIGHT STYLES AND LAYOUT WITH THE CITY OF FRANKLIN PRIOR TO INSTALLATION.
2.	CONTRACTOR SHALL NOTIFY ENGINEER, IF PROOF ROLL OF SUBGRADE FAILS, TO DETERMINE IF LIME STABILIZATION OF SUBGRADE IS NECESSARY.
3.	ALL RADII DIMENSIONS ARE TO THE FACE OF PROPOSED CURB OR EDGE OF PAVEMENT.
4.	SIGNAGE SHALL INCLUDE ALL NECESSARY HARDWARE AND FITTINGS.
5.	CONTRACTOR SHALL BE RESPONSIBLE FOR MAINTAINING TRAFFIC AND PROVIDING ALL NECESSARY FLAGMAN, BARRELS, SIGNAGE, ETC. DURING CONSTRUCTION. ALL APPLICABLE M.U.T.C.D. STANDARDS SHALL GOVERN THIS WORK.
7.	EXISTING UTILITY SIZE AND MATERIAL INFORMATION SHOWN ON THESE PLANS ARE PER THE BEST GRAPHICAL AND VISIBLE INFORMATION AVAILABLE. CONFLICTS MAY EXIST AND IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO FIELD VERIFY ALL SIZING AND MATERIAL INFORMATION PROVIDED. IF ACTUAL CONDITIONS DIFFER FROM THAT INFORMATION SHOWN ON THE PLANS, THE CONTRACTOR SHALL, PRIOR TO THE INSTALLATION OF ANY PROPOSED INFRASTRUCTURE, NOTIFY THE DESIGN ENGINEER IMMEDIATELY.

SANITARY SEWER STRUCTURE TABLE	
STR. DATA	
STR. NO. SS-1	
INSTALL SANITARY DOGHOUSE MANHOLE TYPE 'C' WITH NEENAH R-1772-C CASTING OR AN APPROVED EQUAL. CONNECT TO EXISTING SEWER MAIN AND SANITARY LATERAL.	
RIM=718.33	
INV IN (18°-NW)=710.94	
INV IN (8°-NE)=711.48	
INV OUT (18°-E)=710.94	

PARKING ANALYSIS	
STANDARD PARKING SPACES	= 87 SPACES
A.D.A. ACCESSIBLE SPACES	= 7 SPACES
TOTAL PROPOSED PARKING SPACES	= 94 SPACES

PROPOSED LEGEND	
	CABLE DUCT 4-1/C NO. 4 COPPER CONDUCTORS IN PLASTIC DUCT IN TRENCH
	CABLE DUCT 4-1/C NO. 4 COPPER CONDUCTORS IN PLASTIC DUCT IN 2" GALVANIZED STEEL CONDUIT
	4" PVC CONDUIT
	LIGHTING HANDHOLE
	ORNAMENTAL LUMINAIRE, 16" LIGHT POLE & FOUNDATION
	SANITARY MANHOLE



NOTE: NO EARTHWORK DISTURBING ACTIVITY MAY COMMENCE UNTIL A STORM WATER MANAGEMENT PERMIT IS OBTAINED.	

SITE DIMENSION AND UTILITY PLAN

SOUTH MAIN STREET PARKING LOT

JOB NO.	DRAWN	KLF	CHECKED	TEN	GJ
DATE	JUNE 18, 2018	DESIGNED	DMS	APPR.	

NO.	DATE	REVISIONS
9		
8		
7		
6		
5		
4		
3		
2	08-27-18	REVISIONS PER TRC AND SWPPP COMMENTS RECEIVED 08-23-18 AND 08-27-18
1	07-20-18	REVISIONS PER 08.28.18 DESIGN TEAM MEETING W/CITY OF FRANKLIN

SHEET

300