

# STORMWATER CALCULATIONS

**JOHNSON COUNTY TRAINING FACILITY  
2023 BUILDING ADDITION AND RENOVATION  
1081 HOSPITAL ROAD  
FRANKLIN, INDIANA**

**DRAINAGE SUBMITTAL:  
JUNE 8, 2023**

Prepared By:



CrossRoad Engineers, PC  
115 N. 17th Avenue  
Beech Grove, IN 46107  
Phone No.: (317) 780-1555  
Email: [info@crossroadengineers.com](mailto:info@crossroadengineers.com)

# Table of Contents

## **SECTION 1: STORMWATER CALCULATIONS SUMMARY**

■	PRE-DEVELOPMENT CONDITIONS .....	1
■	POST-DEVELOPMENT CONDITIONS .....	1-2
■	STORM SEWER DESIGN.....	2
■	EXHIBITS	
•	Exhibit 1 – Location and Vicinity Map.....	3
•	Exhibit 2 – Pre-Developed Watershed Map .....	4
•	Exhibit 3 – Post-Developed Watershed Map .....	5
•	FIRM Map .....	6

## **SECTION 2: HYDROLOGIC MODELING CALCULATIONS**

■	SOIL HYDROLOGIC GROUP PERCENTAGE CALCULATIONS.....	7
■	RUNOFF CURVE NUMBER CALCULATIONS	
•	Pre-Development Conditions.....	7
•	Post-Development Conditions .....	7
■	HYDROLOGIC MODELING RUNOFF SUMMARY	
•	Pre-Development Conditions.....	8
•	Post-Development Conditions .....	8
•	Soil Maps .....	9-14

## **SECTION 3: WATER QUALITY CALCULATIONS**

■	WATER QUALITY CALCULATIONS.....	15-24
---	---------------------------------	-------

## **SECTION 4: DETENTION CALCULATIONS**

■	DETENTION CALCULATIONS.....	25-26
---	-----------------------------	-------

## **SECTION 5: STORM SEWER PIPE SIZING CALCULATIONS**

■	PIPE SIZING SUMMARY .....	27
•	Exhibit 5 – Inlet Basin Map .....	28
•	Pipe Sizing Calculations .....	29

## **SECTION 6: STORM INLET/GRATE CALCULATIONS**

■	STORM INLET SUMMARY .....	30-31
---	---------------------------	-------

## **SECTION 1: STORMWATER CALCULATIONS SUMMARY**

### **PRE-DEVELOPMENT CONDITIONS**

The existing site consists of a developed +/-26.7-acre parcel with infrastructure and buildings to the north and a shooting range to the south. The project site is situated on the Johnson County Sheriff's complex located at 1081 Hospital Road, Franklin, Indiana (See Exhibit 1 – Location and Vicinity Map). As described above, the existing land use is built out about the northern portions and contains a shooting range to the south. The existing drainage sheet flows from west to northeast into storm inlets before discharging directly into Young's Creek. Portions of the subject property lie within Flood Hazard Zones X; Shaded X; and AE as plotted by hand on the Federal Emergency Management Agency Flood Insurance Rate Map for Johnson County, Indiana, community panel number 18081C0227E, which bears an effective date of January 29, 2021.

Under pre-developed conditions, runoff exits the site in two different locations. Runoff from the parking area north of the range and the existing storm sewer inlets flow north directly into Young's Creek. Runoff east and southeast of the existing training facility flow east directly into Young's Creek (see Exhibit 2 – Pre-Developed Watershed Map). For the runoff and detention analysis, the calculations focus solely on the watershed captured by the existing inlets and the areas where the impervious improvements will be made. The existing parking area and training center building will not be included in the post-development calculations.

### **POST-DEVELOPMENT CONDITIONS**

The proposed improvements in this phase of the project include the renovation of the existing training facility and various site improvements in preparation for a future building addition. These improvements will also include the underground detention basin required to detain the runoff created by the new building addition and access road that will be built in phase 2 of this project. Along with those improvements, utility relocations, new storm sewer, modifications to the gun range, and various site grading to prepare for the future building addition will also be included. The proposed site grading results in runoff sheet flowing from west to east and from west to northeast into the proposed storm network west of the existing training center building. The proposed underground detention system will provide stormwater quantity and quality treatment in accordance with Section 6.19 of the City of Franklin Subdivision Control Ordinance (see Exhibit 3 – Post-Developed Watershed Map).

As described in the Pre-Development Conditions above, only the areas captured by the existing inlets, as well as the new impervious areas created by the building addition and access road will drain into the proposed underground detention system. The underground detention system will then discharge directly into Young's Creek. To achieve water quantity detention standards, the detention system and outlet structure will be sized to restrict the peak discharge rate of the 10-year post-developed storm for the site to the peak 2-year pre-developed rate. Additionally, the peak discharge rate of the 100-year post-developed storm will be restricted to the peak 10-year pre-development discharge rate.

The proposed underground detention system will also be designed to detain at least 20% of the runoff from either the 1.25" rainfall depth storm or 0.5" of direct runoff, whichever is greater, for 24 hours after the peak runoff from a 24-hour storm for water quality treatment. The outlet structure of the underground detention system will be designed to include an emergency overflow spillway that is sufficient to convey 1.25 times the peak discharge from the 100-year post-development storm. The underground detention system will be designed to meet the requirement of Section 6.19, G and H of the City of Franklin Subdivision Control Ordinance.

### **STORM SEWER DESIGN**


The proposed storm sewer network is designed to accommodate the 10-year storm event. The Rational Method was used to perform the storm sewer pipe sizing calculations. The structures and grates in the paved areas were designed so that the depth of ponding above the inlet does not exceed 6 inches when the grate is 50% plugged. Inlets within grass areas were designed so that the depth of ponding above the inlet does not exceed 9 inches when the grate is 50% plugged.



# **EXHIBIT 1 - LOCATION AND VICINITY MAPS**


## **JOHNSON COUNTY TRAINING CENTER**

### **1081 HOSPITAL ROAD, FRANKLIN, IN**



**LOCATION MAP**

NOT TO SCALE



**VICINITY MAP**

NOT TO SCALE

PREPARED BY:





Transportation &  
Development Consultants  
100 N. 10th Street, Suite 200, Franklin, IN 47301  
JUNE 8, 2023

# EXHIBIT 2 - PRE-DEVELOPMENT WATERSHED MAP

## JOHNSON COUNTY TRAINING FACILITY

### 1081 HOSPITAL ROAD



PREPARED BY:



Transportation &  
Development Consultants

115 N. 17th Avenue, Beech Grove, IN 46107 (317) 786-1555

JUNE 8, 2023



# EXHIBIT 3 - POST-DEVELOPMENT WATERSHED MAP

## JOHNSON COUNTY TRAINING FACILITY

### 1081 HOSPITAL ROAD



PREPARED BY:



Transportation &  
Development Consultants  
115 N. 17th Avenue, Beech Grove, IN 46107 (317) 780-1555

JUNE 8, 2023



# National Flood Hazard Layer FIRMette



86°4'49"W 39°28'46"N



## Legend

SEE FIS REPORT FOR DETAILED LEGEND AND INDEX MAP FOR FIRM PANEL LAYOUT

SPECIAL FLOOD HAZARD AREAS		Without Base Flood Elevation (BFE) Zone A, V, A99
		With BFE or Depth Zone AE, AO, AH, VE, AR
		Regulatory Floodway
OTHER AREAS OF FLOOD HAZARD		0.2% Annual Chance Flood Hazard, Areas of 1% annual chance flood with average depth less than one foot or with drainage areas of less than one square mile Zone X
		Future Conditions 1% Annual Chance Flood Hazard Zone X
		Area with Reduced Flood Risk due to Levee. See Notes. Zone X
		Area with Flood Risk due to Levee Zone D
OTHER AREAS		NO SCREEN Area of Minimal Flood Hazard Zone X
		Effective LOMRs
GENERAL STRUCTURES		Area of Undetermined Flood Hazard Zone D
		Channel, Culvert, or Storm Sewer
		Levee, Dike, or Floodwall
OTHER FEATURES		20.2 Cross Sections with 1% Annual Chance Water Surface Elevation
		17.5 Cross Sections with 1% Annual Chance Water Surface Elevation
		Coastal Transect
		Base Flood Elevation Line (BFE)
		Limit of Study
		Jurisdiction Boundary
MAP PANELS		Coastal Transect Baseline
		Profile Baseline
		Hydrographic Feature
		Digital Data Available
		No Digital Data Available
		Unmapped



The pin displayed on the map is an approximate point selected by the user and does not represent an authoritative property location.

This map complies with FEMA's standards for the use of digital flood maps if it is not void as described below. The basemap shown complies with FEMA's basemap accuracy standards

The flood hazard information is derived directly from the authoritative NFHL web services provided by FEMA. This map was exported on 4/7/2023 at 8:26 AM and does not reflect changes or amendments subsequent to this date and time. The NFHL and effective information may change or become superseded by new data over time.

This map image is void if the one or more of the following map elements do not appear: basemap imagery, flood zone labels, legend, scale bar, map creation date, community identifiers, FIRM panel number, and FIRM effective date. Map images for unmapped and unmodernized areas cannot be used for regulatory purposes.

## SECTION 2: HYDROLOGIC MODELING CALCULATIONS

As previously noted, all stormwater calculations were completed using rational method. The time of concentration for each inlet was calculated using the TR-55 method. Curve numbers were computed based on the applicable cover for fully developed urban areas and the percentage area of each hydrologic soil type obtained from the USDA Web Soils Survey for the project area.

### Soil Hydrologic Group Percentage Calculations:

<b>Table 1</b>		
<b>Soil Hydrologic Group Percentage Calculations – Pre-Developed</b>		
<b>Soil Type</b>	<b>Hydrologic Group – B (acres)</b>	<b>Hydrologic Group – C (acres)</b>
Crosby, YclA	--	0.541
Miami Silt, YmsB2	--	0.588
Miami Silt, YmsC2	--	0.187
<b>Totals</b>	--	1.316
<b>Percentages of Hydrologic Groups</b>	<b>0%</b>	<b>100%</b>

<b>Table 2</b>		
<b>Soil Hydrologic Group Percentage Calculations – Post-Developed</b>		
<b>Soil Type</b>	<b>Hydrologic Group – B (acres)</b>	<b>Hydrologic Group – C (acres)</b>
Crosby, YclA	--	0.543
Miami Silt, YmsB2	--	0.592
Miami Silt, YmsC2	--	0.187
<b>Totals</b>	--	1.322
<b>Percentages of Hydrologic Groups</b>	<b>0%</b>	<b>100%</b>

### Pre-Development Conditions

<b>Table 3</b>						
<b>Pre-Development Runoff Curve Number Calculations</b>						
<b>Land Use Description</b>	<b>Runoff Curve No. For Hydrologic Group – B</b>		<b>Runoff Curve No. For Hydrologic Group – C</b>		<b>Average Runoff Curve Number</b>	<b>Land Use Area</b>
	<b>Percentage Used*</b>	<b>0%</b>	<b>Percentage Used*</b>	<b>100%</b>		
Pavement	98		98		98	0.365 Ac.
Open Space	61		74		74	0.951 Ac.
						<b>80.66</b>

\*See Soil Hydrologic Group Percentage Calculations, Table 1.

### Post-Development Conditions

<b>Table 4</b>						
<b>Post-Development Runoff Curve Number Calculations</b>						
<b>Land Use Description</b>	<b>Runoff Curve No. For Hydrologic Group – B</b>		<b>Runoff Curve No. For Hydrologic Group – C</b>		<b>Average Runoff Curve Number</b>	<b>Land Use Area</b>
	<b>Percentage Used*</b>	<b>0%</b>	<b>Percentage Used*</b>	<b>100%</b>		
Pavement	98		98		98	0.521 Ac.
Open Space	61		74		74	0.801 Ac.
						<b>83.46</b>

\*See Soil Hydrologic Group Percentage Calculations, Table 2.



## **HYDROLOGIC MODELING RUNOFF SUMMARY**

### **PRE-DEVELOPMENT CONDITIONS**

The City of Franklin Subdivision Control Ordinance requires a detention design that outlets stormwater at the following rates:

<u>Post-Development:</u>		<u>Pre-Development:</u>
Post 10-yr Q	≤	Pre 2-yr Q
Post 100-yr Q	≤	Pre 10-yr Q

The City of Franklin requires that the 10-year and 100-year post-development rain events shall be limited to the pre-developed 2-year and 10-year rain events, respectively. The City of Franklin Subdivision Control Ordinance requires that the storm events are calculated at durations of 1, 2, 3, 6, 12, and 24 hours to identify the critical storm events which are to be used for the respective limiting pre-development rates; however, only the 24-hour storm was calculated, as it is customary that the peak runoff is generated during the 24-hour event using the SCS Type II rainfall distribution. Table 3 summarizes the peak runoff rates (cfs) resulting from the hydrologic modeling of the Pre-Development Watershed Basin which is representative of the contributing watershed area in the existing condition. Runoff rates were only calculated for the areas collected by the existing storm sewer system as the allowable release rates will be determined based on that watershed only. See Appendix A for the pre-developed hydrograph and peak storm event analysis results.

<b>Table 3</b>	
<b>Pre-Development Watershed Hydrograph Peak Runoff Rate Summary</b>	
<b>Return Period (years)</b>	<b>Storm Duration</b>
	24 Hours
2	<b>1.92 cfs</b>
10	<b>3.38 cfs</b>

#### **Basin Allowable Discharge:**

**Allowable discharge for the critical 10-year post-development storm=**  
**Pre-Development 2-year Peak = 1.92 cfs**

**Allowable discharge for the critical 100-year post-development storm=**  
**Pre-Development 10-year Peak = 3.38 cfs**

### **POST-DEVELOPMENT CONDITIONS**

Table 4 summarizes the peak runoff rates resulting from the hydrologic modeling of the Post-Development Watershed Basin which is representative of the contributing watershed area in the proposed condition. See Appendix B for the post-development hydrographs and peak storm event analysis results.

<b>Table 4</b>	
<b>Post-Development Watershed Hydrograph Peak Runoff Rate Summary</b>	
<b>Return Period (years)</b>	<b>Storm Duration</b>
	24 Hours
10	<b>4.15 cfs</b>
100	<b>6.92 cfs</b>

# Soil Map—Johnson County, Indiana




## MAP LEGEND

### Area of Interest (AOI)

 Area of Interest (AOI)

### Soils

 Soil Map Unit Polygons

 Soil Map Unit Lines

 Soil Map Unit Points

### Special Point Features



Blowout



Borrow Pit



Clay Spot



Closed Depression



Gravel Pit



Gravelly Spot



Landfill



Lava Flow



Marsh or swamp



Mine or Quarry



Miscellaneous Water



Perennial Water



Rock Outcrop



Saline Spot



Sandy Spot



Severely Eroded Spot



Sinkhole



Slide or Slip



Sodic Spot



Spoil Area



Stony Spot



Very Stony Spot



Wet Spot



Other



Special Line Features

### Water Features



Streams and Canals

### Transportation



Rails



Interstate Highways



US Routes



Major Roads



Local Roads

### Background



Aerial Photography

## MAP INFORMATION

The soil surveys that comprise your AOI were mapped at 1:15,800.

Warning: Soil Map may not be valid at this scale.

Enlargement of maps beyond the scale of mapping can cause misunderstanding of the detail of mapping and accuracy of soil line placement. The maps do not show the small areas of contrasting soils that could have been shown at a more detailed scale.

Please rely on the bar scale on each map sheet for map measurements.

Source of Map: Natural Resources Conservation Service

Web Soil Survey URL:

Coordinate System: Web Mercator (EPSG:3857)

Maps from the Web Soil Survey are based on the Web Mercator projection, which preserves direction and shape but distorts distance and area. A projection that preserves area, such as the Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required.

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: Johnson County, Indiana

Survey Area Data: Version 30, Sep 3, 2022

Soil map units are labeled (as space allows) for map scales 1:50,000 or larger.

Date(s) aerial images were photographed: Jun 15, 2022—Jun 21, 2022

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.



## Map Unit Legend

Map Unit Symbol	Map Unit Name	Acres in AOI	Percent of AOI
YclA	Crosby silt loam, fine-loamy subsoil-Urban land complex, 0 to 2 percent slopes	0.5	41.1%
YmsB2	Miami silt loam-Urban land complex, 2 to 6 percent slopes, eroded	0.6	44.7%
YmsC2	Miami silt loam-Urban land complex, 6 to 12 percent slopes, eroded	0.2	14.2%
<b>Totals for Area of Interest</b>		<b>1.3</b>	<b>100.0%</b>

Soil Map—Johnson County, Indiana




## MAP LEGEND

### Area of Interest (AOI)

 Area of Interest (AOI)

### Soils

 Soil Map Unit Polygons

 Soil Map Unit Lines

 Soil Map Unit Points

### Special Point Features



Blowout



Borrow Pit



Clay Spot



Closed Depression



Gravel Pit



Gravelly Spot



Landfill



Lava Flow



Marsh or swamp



Mine or Quarry



Miscellaneous Water



Perennial Water



Rock Outcrop



Saline Spot



Sandy Spot



Severely Eroded Spot



Sinkhole



Slide or Slip



Sodic Spot



Spoil Area



Stony Spot



Very Stony Spot



Wet Spot



Other



Special Line Features

### Water Features



Streams and Canals

### Transportation



Rails



Interstate Highways



US Routes



Major Roads



Local Roads

### Background



Aerial Photography

## MAP INFORMATION

The soil surveys that comprise your AOI were mapped at 1:15,800.

Warning: Soil Map may not be valid at this scale.

Enlargement of maps beyond the scale of mapping can cause misunderstanding of the detail of mapping and accuracy of soil line placement. The maps do not show the small areas of contrasting soils that could have been shown at a more detailed scale.

Please rely on the bar scale on each map sheet for map measurements.

Source of Map: Natural Resources Conservation Service

Web Soil Survey URL:

Coordinate System: Web Mercator (EPSG:3857)

Maps from the Web Soil Survey are based on the Web Mercator projection, which preserves direction and shape but distorts distance and area. A projection that preserves area, such as the Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required.

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: Johnson County, Indiana

Survey Area Data: Version 30, Sep 3, 2022

Soil map units are labeled (as space allows) for map scales 1:50,000 or larger.

Date(s) aerial images were photographed: Jun 15, 2022—Jun 21, 2022

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.

## Map Unit Legend

Map Unit Symbol	Map Unit Name	Acres in AOI	Percent of AOI
YclA	Crosby silt loam, fine-loamy subsoil-Urban land complex, 0 to 2 percent slopes	0.5	41.0%
YmsB2	Miami silt loam-Urban land complex, 2 to 6 percent slopes, eroded	0.6	43.7%
YmsC2	Miami silt loam-Urban land complex, 6 to 12 percent slopes, eroded	0.2	15.3%
<b>Totals for Area of Interest</b>		<b>1.3</b>	<b>100.0%</b>

### SECTION 3: WATER QUALITY CALCULATIONS

The City of Franklin Subdivision Control Ordinance requires all paved areas to be routed through a water quality detention system. The water quality detention system shall be designed to detain, for over 24 hours after peak runoff, at least 20% of the volume of runoff from a 1 ¼" rainfall depth storm or 0.5" of direct runoff, whichever is greater. The minimum water quality outlet shall be 2" in diameter. See Appendix B for the water quality hydrograph results, additional water quality data, routed water quality hydrograph, and Exhibit 4 – Water Quality Watershed Map.

#### WATER QUALITY VOLUME

Volume of Runoff from 1 ¼" Rainfall Depth Storm,  $V_1 = 1,237 \text{ ft}^3 = 0.028 \text{ ac.-ft}$

Volume of Runoff from 0.5" Direct Runoff,

$$V_2 = 1.32 \text{ ac.} * (0.5"/12) = \underline{\underline{0.055 \text{ ac.-ft}}}$$

Water Quality Volume,  $WQ_v = 20\% * V_2 = 0.2 * 0.055 \text{ ac.-ft} = \underline{\underline{0.011 \text{ ac.-ft} \rightarrow 480 \text{ ft}^3}}$

At a time of 24 hours after the peak runoff rate of the inflow hydrograph, the detention system must have at least 0.011 ac.-ft or 480 ft<sup>3</sup> remaining in the basin.

#### ROUTED WATER QUALITY STORM HYDROGRAPH

The 0.5" direct runoff storm event is routed through the proposed detention system with a 2" diameter circular water quality orifice. The Routed 0.5" Storm Event Hydrograph is used to verify the water quality volume,  $WQ_v$ , remaining after 24 hours past peak runoff.

Table 7 Water Quality Volume Summary		
	Time	Volume
Time to Peak	12.83 hours	935 ft <sup>3</sup>
Maximum Time where $WQ_v$ is Detained	16.00 hours	487 ft <sup>3</sup>
Storage Volume at Time of 24 hours Past Peak Runoff	36.83 hours	5 ft <sup>3</sup>

The minimum 2" diameter water quality orifice is not small enough to detain the required water quality volume for the minimum 24 hours. The water quality volume can be detained for 3.17 hours utilizing the 2" water quality orifice.

#### SUPPLEMENTAL WATER QUALITY INFORMATION


Since the proposed detention system is an underground system, more information has been provided on the function and water quality treatment the proposed isolator rows provide. Per literature available from ADS Stormtech's website, the Isolator Row Plus has been tested and NJCAT verified to remove 81% Total Suspended Solids. The minimum 80% TSS removal is achieved by sizing the Isolator Row Plus to treat the water quality at a specific flow rate per chamber floor area using a single layer of ADS PLUS fabric. The design flow rate for a StormTech MC-3500 chamber is 0.40 cfs / chamber. Each MC-3500 chamber can treat a flow rate of 0.40 cfs.

Using the 0.5" direct runoff storm event, the water quality flow rate generated is 0.79 cfs. In order to meet the minimum 80% TSS removal rate, a minimum of 2 chambers in the isolator rows are required. With the one isolator row, 6 chambers are provided which correlates to a treated flow rate of 2.40 cfs.

The Summary of Testing literature can be found within this section.



**EXHIBIT 4 - WATER QUALITY WATERSHED MAP**  
**JOHNSON COUNTY TRAINING FACILITY**  
**1081 HOSPITAL ROAD**




PREPARED BY:



Transportation &  
Development Consultants  
115 N. 17th Avenue, Beech Grove, IN 46107 (317) 786-1555

JUNE 8, 2023


## Routed 0.5" WQ Storm Runoff Hydrograph and Results



Element ID	Out-03
Maximum Total Inflow (cfs)	0.79
Minimum Total Inflow (cfs)	0.00
Event Mean Total Inflow (cfs)	0.01
Duration of Exceedances (hrs)	N/A
Duration of Deficits (hrs)	N/A
Number of Exceedances	N/A
Number of Deficits	N/A
Volume of Exceedance (ft³)	N/A
Volume of Deficit (ft³)	N/A
Total Inflow Volume (ft³)	<b>2399.44</b>
Detention Storage (ft³)	N/A
Exceedance	0
Deficit	0



## Routed 0.5" WQ Storm Pond Volume Hydrograph and Results



Element ID	Stor-02
Maximum Volume (ft³)	934.35
Minimum Volume (ft³)	0.00
Event Mean Volume (ft³)	66.91
Duration of Exceedances (hrs)	N/A
Duration of Deficits (hrs)	N/A
Number of Exceedances	N/A
Number of Deficits	N/A
Exceedance	0
Deficit	0

# Summary of Testing


## StormTech® Isolator® Row Plus – Pollutant Removal

The following information is intended to provide a general overview of the pollutant removal capability of the StormTech Isolator Row Plus, which is a patented filtration type BMP manufactured by StormTech, LLC. The StormTech Isolator Row Plus is covered under several US and International patents.

### I. Description:

The StormTech Isolator Row Plus is a row or rows of thermoplastic chambers that sit on a layer of ADS Plus fabric and are connected to a closely located structure for easy access. The chambers provide for settling and filtration of sediment and other contaminants as stormwater rises in the Isolator Row Plus and ultimately passes through the fabric. The open-bottom chambers allow stormwater to flow out of the chambers. Sediment is captured in the Isolator Row Plus, protecting the storage areas of the adjacent stone and chambers from sediment accumulation. The StormTech Isolator Row Plus is designed to capture the “first flush” and offers the versatility to be sized on a volume basis or a flow-rate basis. An upstream manhole not only provides access to the Isolator Row but includes a high low/concept such that stormwater flow rates or volumes that exceed the capacity of the Isolator Row bypass through a manifold to the other chambers. This is achieved with either a high-flow weir or an elevated manifold. This creates a differential between the Isolator Row Plus and the manifold, thus allowing for settlement time in the Isolator Row Plus.


**Figure 1: Schematic of the StormTech Isolator Row Plus System**



Some of the unique features of the Isolator Row that contribute to its effectiveness and practicality include:

- Vast filtration surface area
- Large sediment storage volume
- Easily maintainable by most pipe and sewer maintenance companies
- Large network of ADS personnel that can help with designs and provide onsite guidance
- A state-of-the-art structural design that meets ASTM standards and incorporates AASHTO safety factors for both live loads and permanent dead loads

**Figure 2: Isolator Row Plus Cross Section Detail**



## II. Applicable Sites:

The Isolator Row Plus can be effectively used for essentially all developed sites. The most common applications are highly impervious sites such as paved parking areas, roads as well as developed sites that include grassy or other landscaped areas. It is not intended to be used for construction sediments.

## III. StormTech System & Isolator Row Testing:

**October 2006** – Tennessee Tech University’s Civil and Environmental Department prepared the “Performance Evaluation of Sediment Removal Efficiency – StormTech Isolator Row”. Testing on a full-scale Isolator Row in a laboratory was done to determine the sediment removal efficiency with two different silica-water slurries in accordance with NJCAT protocols. In August of 2007, the technology was verified by NJCAT. Results are shown in Table 1.

**September 2010** – The University of New Hampshire Stormwater Center released the “Final Report on Field Verification Testing of the StormTech Isolator Row Treatment Unit”. Testing consisted of determining the water quality performance for multiple stormwater pollutants in accordance with TARP Tier II protocol. Testing was done for a system only consisting of the StormTech Isolator Row. Data was recorded for 23 storm events. Results are shown in Table 1.

**January 2020** – BaySaver Technologies prepared the “NJCAT Technology Verification of Isolator Row Plus”. Testing on a full-scale Isolator Row Plus in a laboratory was done to determine the sediment removal efficiency with a silica-water slurry in accordance with the updated NJCAT protocols. In July of 2020, the technology was verified by NJCAT. Results are shown in Table 1.

**June 2020** – North Carolina State University Department of Biological and Agricultural Engineering prepared the technical report “An Evaluation of the StormTech Isolator Row and Subsurface Stormwater Management System at Capital Oaks Retirement Resort, Raleigh, North Carolina”. 14 months of monitoring and over 73 precipitation events were completed to study the hydrologic and water quality performance of a StormTech MC-4500 system in Raleigh, NC. Results are shown in Table 1.

**Table 1: StormTech Isolator Row 3<sup>rd</sup> Party Pollutant Removal Efficiency Data**

Pollutant	University of New Hampshire (Isolator Row Only) Median	Raleigh, North Carolina (StormTech system with Isolator Row)	Tennessee Tech University (Isolator Row Only)	NJCAT Verification (Isolator Row Plus only)
Total Suspended Solids	83%*	91%*	84%*	81%**
Total Phosphorus	33%	68%	Not Tested	Not Tested
Total Nitrogen	Not Tested	35%	Not Tested	Not Tested
Total Zinc	81%	Not Tested	Not Tested	Not Tested
Total Petroleum Hydrocarbons	91%	Not Tested	Not Tested	Not Tested

\*Based on a flow rate of 2.5 gpm/sf (1.70 L/s/m<sup>2</sup>) (Isolator Row)

\*\* Based on a flow rate of 4.1 gpm/sf (2.78 L/s/m<sup>2</sup>) (Isolator Row Plus)

## IV. Product Performance and Design:

Minimum 80% TSS removal is achieved by sizing the Isolator Row PLUS to treat the water quality at a specific flow rate per chamber floor area using a single layer of ADS Plus fabric. The design flow rates for each chamber size are listed below.

Model	Specific Flow Rate	Bottom Area	Flow Per Model
StormTech SC-160LP	4.1 gpm/sf (2.78 L/s/m <sup>2</sup> )	11.45 sf (1.06 m <sup>2</sup> )	0.11 cfs (3.11 L/s)
StormTech SC-310	4.1 gpm/sf (2.78 L/s/m <sup>2</sup> )	17.7 sf (1.64 m <sup>2</sup> )	0.16 cfs (4.53 L/s)
StormTech SC-740	4.1 gpm/sf (2.78 L/s/m <sup>2</sup> )	27.8 sf (2.58 m <sup>2</sup> )	0.26 cfs (7.36 L/s)
StormTech DC-780	4.1 gpm/sf (2.78 L/s/m <sup>2</sup> )	27.8 sf (2.58 m <sup>2</sup> )	0.26 cfs (7.36 L/s)
StormTech MC-3500	4.1 gpm/sf (2.78 L/s/m <sup>2</sup> )	42.9 sf (3.99 m <sup>2</sup> )	0.40 cfs (11.33 L/s)
StormTech MC-4500	4.1 gpm/sf (2.78 L/s/m <sup>2</sup> )	30.1 sf (2.80 m <sup>2</sup> )	0.28 cfs (7.93 L/s)
StormTech MC-7200	4.1 gpm/sf (2.78 L/s/m <sup>2</sup> )	50.0 sf (4.65 m <sup>2</sup> )	0.45 cfs (12.74 L/s)



## V. StormTech Isolator Row Approvals:

The StormTech Isolator Row and Isolator Row Plus have been approved on a project by project basis for tens of thousands of projects around the world. Following are some examples:

- The Isolator Row Plus is a verified filtration manufactured treatment device by the New Jersey Corporation for Advanced Testing (NJCAT) in accordance with NJDEP Filter Protocols.
- In Ohio, the Isolator Row is approved per the Ohio EPA as a pretreatment to underground storage and can be used for both storage volume and pretreatment as the water quality volume all passes through the Isolator Row.
- The Metropolitan St. Louis Sewer District (MSD) has approved the StormTech Isolator Row as a standalone post-construction stormwater Best Management Practice.
- In Massachusetts, approvals for the State DEP requirement of 80% TSS removal on an annual load basis are issued at the Conservation Commission level, and the Isolator Row is commonly used to meet these criteria.
- In Oregon, the Rogue Valley Storm Water Advisory Team (SWAT) has incorporated the StormTech Isolator Row into their Stormwater Design Manual as a pre-approved proprietary device for stormwater quality treatment.
- The Kansas City Metro Chapter of the American Public Works have included the StormTech Isolator Row with a value rating of 3.0 in their Manual of Best Management Practices for Stormwater Quality.
- Maine DEP has approved the Isolator Row pollutant removal efficiency based on laboratory testing of 110 micron (US Silica OK-110) particle size
- In Texas, the City of Houston PWE as well as Harris county, has recognized the Isolator Row as an official water quality device.
- Under the New Environmental Technology Evaluation program, the Ontario (Canada) Ministry of the Environment has evaluated the Isolator row and issued a Certificate of Technology Assessment
- The Isolator Row Plus has been evaluated and approved for Canadian Environment Technology Verification (ETV) by VerifiGlobal.

## V. Isolator Row Maintenance:

The frequency of Inspection and Maintenance varies by location. A routine inspection schedule needs to be established for each individual location, based upon site-specific variables. The type of land use (i.e. industrial, commercial, public, residential), anticipated pollutant load, percent imperviousness, climate, rainfall data, etc., all play a critical role in determining the actual frequency of inspection and maintenance practices.

At a minimum, StormTech recommends annual inspections. Initially, the Isolator Row should be inspected every 6 months for the first year of operation. For subsequent years, the inspection schedule should be adjusted based upon previous observation of sediment deposition.

The Isolator Row incorporates a combination of standard manhole(s) and strategically located inspection ports (as needed). The inspection ports allow for easy access to the system from the surface, eliminating the need to perform a confined space entry for inspection purposes.

If, upon visual inspection, it is found that sediment has accumulated, a stadia rod should be inserted to determine the depth of sediment. When the average depth of sediment exceeds 3 inches throughout the length of the Isolator Row, clean-out should be performed.

The Isolator Row was designed to reduce the cost of periodic maintenance. By “isolating” sediment to just one row, costs are dramatically reduced by eliminating the need to clean out



each row of the entire storage bed. If inspection indicates the potential need for maintenance, access is provided via a manhole(s) located on the end(s) of the row for cleanout.

Maintenance is accomplished with the jetvac process. The jetvac process utilizes a high-pressure water nozzle to propel itself down the Isolator Row while scouring and suspending sediment. As the nozzle is retrieved, the captured pollutants are flushed back into the manhole for vacuuming. Most sewer and pipe maintenance companies have vacuum/jetvac combination vehicles. Selection of an appropriate jetvac nozzle will improve maintenance efficiency.

Fixed nozzles designed for culverts or large diameter pipe cleaning are preferable. Rear-facing jets with an effective spread of at least 45" are best. Most jetvac reels have 200 feet of hose, allowing maintenance of an Isolator Row up to 50 chambers long. The jetvac process shall only be performed on StormTech Isolator Rows that have fabric specified by StormTech over their angular base stone.

Complete details of the design, operation, and maintenance of the Isolator Row Plus can be found in the StormTech Isolator Row and Isolator Row Plus O&M Manuals.





## SECTION 4: DETENTION CALCULATIONS

Per ordinance, stormwater detention is addressed by restricting the release rates of runoff previously described in Section 2: Hydrologic Modeling Calculations. The following information is provided as verification that the proposed wet detention ponds and outlet structure are capable of detaining and restricting the release rates of runoff from the post-developed site.

### Allowable Discharge Rate (see Section 2: Hydrologic Modeling Calculations, Hydrologic Modeling Runoff Summary)

Allowable discharge for the critical 10-year post-development storm =  
Pre-Development 2-year Peak = **1.92 cfs**

Allowable discharge for the critical 100-year post-development storm =  
Pre-Development 10-year Peak = **3.38 cfs**

### Post-Development Peak Flowrate (see Section 2: Hydrologic Modeling Calculations, Hydrologic Modeling Runoff Summary)

Post-Development Watershed:

$Q_{10} = 4.15 \text{ cfs}$

$Q_{100} = 6.92 \text{ cfs}$

### Outlet Structure Summary (see Appendix C: Post-Development Runoff & Routed Storm Data)

The proposed outlet structure shall utilize a Modified Inlet Type "E" with one (1) circular 2" diameter orifice to meet the water quality requirements, one (1) circular 7.00" diameter orifice to meet allowable discharge requirements for 10-year critical storm events, and one (1) 3" x 6" rectangular orifice to meet the detention and allowable discharge requirements for 100-year critical storm events. Discharge will be conveyed directly into Young's Creek to the north via a proposed 18" diameter outlet pipe leaving the outlet control structure.

### Routed Storm Hydrographs (see Appendix C: Post-Developed Runoff & Routed Storm Data)

Peak 10-Year Post-Development Discharge Rate = **1.72 cfs**  $\leq 1.92 \text{ cfs}$  (allowable)

Peak Water Surface Elevation = **727.87**  $< 729.65$  (top of emergency spillway)

Peak 100-Year Post-Development Discharge Rate = **3.37 cfs**  $\leq 3.38 \text{ cfs}$  (allowable)

Peak Water Surface Elevation = **729.65**  $< 729.65$  (top of emergency spillway)

**All post-development storms are discharged at a flowrate less than their respective allowable discharge rates. All post-development storms produce a water surface elevation below the maximum detention system elevation.**

## Emergency Scenario

An emergency overflow weir will be constructed inside of the outlet control structure in the event that the control orifices become clogged and inoperable. The emergency weir was designed to convey  $1.25 \times Q_{100}$  where  $Q_{100}$  equals the peak 100-year inflow to the basin from the entire contributing watershed. The spillway will ultimately discharge into Young's Creek north of the site. Below are calculations for the emergency spillway:

$Q_{100}$  Inflow = 6.92 cfs

$1.25 \times Q_{100}$  Inflow = 8.65 cfs

Length of Weir = 4.5 ft. (min.)

Top of Detention Basin Elevation = 730.70

Spillway Crest Elevation = 729.65

Water Surface Elevation = 730.35

$$H = [(1.25 \times Q_{100}) / (3.3 \times L)]^{2/3} = [8.65 / (3.3 \times 4.5)]^{2/3} = 0.70'$$

The head needed to convey the required flowrate is 0.70'. The corresponding elevation is 730.35, which means the emergency elevation is still contained within the limits of the detention system. It does not exceed the elevation of the top of the stone and will not cause any surcharging of the outlet structure or any structures upstream.



## **SECTION 5: STORM SEWER PIPE SIZING CALCULATIONS**


The storm sewer was designed to convey via gravity the peak runoff from the 10-year storm event. Additionally, the storm sewer was designed such that the hydraulic grade line resulting from the 100-year storm event does not surcharge above the rim elevation at the storm structures. However, as an additional measure of protection, the pipes downstream of the detention system's outlet structure were sized to convey the 100-year flow leaving the detention system. All drainage calculations were completed using the Rational Method. The time of concentration was calculations and composite runoff coefficient calculations are also included in Appendix A.

Structure	Pipe Data						Inlet Watershed Data										Contributing Watershed Data						Pipe Analysis					
	Downstream Structure	Length (ft)	Pipe Diameter (in)	Pipe Material	Invert Slope (%)	Mannings Number n	Catchment Area (ac) Conc/Roof	Runoff Coefficient C Conc/Roof	Catchment Area (ac) Asphalt	Runoff Coefficient C Asphalt	Catchment Area (ac) Grass	Runoff Coefficient C Grass	Total Area A (ac)	Composite Coefficient C	Tc (min)	Rainfall Intensity (I) in/hr	Manual Input Flow Q (cfs)	10-yr Q=CiA (cfs)	Total Area A (ac)	Runoff Coefficient C	Time in Upstream Pipe (min)	Total Time of Concentration Tc (min)	Intensity I (in/hr)	Total 10-yr Pipe Flow (cfs)	Pipe Capacity Qmax (cfs)	Full Flow Pipe Velocity (ft/s)	% of Full Flow Capacity	
1	2	83	12	RCP	0.25	0.013	0.110	0.85	0.000	0.82	0.182	0.20	0.293	0.45	12.18	5.13	0	0.67	0.29	0.45	--	12.18	5.13	0.67	1.90	2.55	35.23%	
2	3	--	15	RCP	0.36	0.013	0.131	0.85	0.279	0.82	0.619	0.20	1.029	0.45	12.59	5.05	0	2.34	1.32	0.45	0.54	12.72	5.03	2.99	7.00	3.06	42.67%	
3	4	19	18	RCP	0.63	0.013	0.000	0.85	0.000	0.82	0.000	0.20	0.000	--	--	--	0	8.65	1.32	--	--	--	--	--	8.65	8.89	5.30	97.34%
4	5	56	18	RCP	0.65	0.013	0.000	0.85	0.000	0.82	0.000	0.20	0.000	--	--	--	0	8.65	1.32	--	--	--	--	--	8.65	9.03	5.39	95.83%
5	ES	73	24	RCP	0.30	0.013	0.000	0.85	0.117	0.82	0.509	0.20	0.626	0.32	10.08	5.55	8.65	1.10	0.63	0.32	0.17	10.25	5.52	9.74	13.21	4.43	73.75%	

# EXHIBIT 5 - INLET WATERSHED MAP

## JOHNSON COUNTY TRAINING FACILITY

### 1081 HOSPITAL ROAD



PREPARED BY:



Transportation &  
Development Consultants  
115 N. 17th Avenue, Beech Grove, IN 46107 (317) 780-1555

JUNE 8, 2023

## SECTION 6: STORM INLET/GRATE CALCULATIONS

Storm inlets were placed throughout the site to ensure that the sag inlets will be adequate to pass the design 10-year flow with 50% of the inlet clogged and with the maximum depth of water not exceeding six (6) inches in paved areas and nine (9) inches in swales/yard areas. The castings used for this project are listed in the table below (Table 5) along with the inlet grate perimeter and open area dimensions per the Neenah Foundry catalog.

The following table (Table 5) indicates the maximum inlet/grate capacity for all inlets in this development. Refer to Appendix A for the grate capacity calculations.

**Table 5: Grate Capacity**

<b>Structure No.</b>	<b>Casting Type</b>	<b>Watershed Runoff</b>	<b>Max. Allowable Ponding Depth</b>	<b>Total Flow Intercepted</b>	<b>Max. Grate Capacity @ 50% Clogged</b>
1	R-4215-C	0.67 cfs	9"	0.67 cfs	6.99 cfs
2	R-3405	2.34 cfs	6"	2.34 cfs	2.59 cfs
5	R-4215-C	1.10 cfs	9"	1.48 cfs	6.99 cfs

**Sag Inlet Capacity Worksheet****Project:** Johnson County Training Facility**Computed By:** BTV**Date:****6/8/2023**

Inlet Casting Information					
Type	Width (ft)	Length (ft)	P (ft)	A (sq. ft.)	Depression (in)
R-3405	1.97	1.97	7.9	1.5	N/A
R-4215-C	2.83	2.83	11.3	3.3	N/A

Inlet Grate Design Parameters		
Type	Max. Spread (ft)	Max. Ponding Depth (ft)
Sag Inlet	N/A	0.50

0.75

**SAG INLETS**

Structure	Casting Type	10-yr Inlet Watershed Flow (cfs)	50% Wetted Perimeter (ft.)	50% Open Area (sq. ft.)	Max. Allowable Ponding (ft)	Max. Allowable Flow w/50% Clogged (cfs)	10-yr Actual Ponding (Weir Equ)	10-yr Actual Ponding (Orifice Equ)	Check Casting
1	R-4215-C	0.67	5.65	1.65	0.75	6.99	0.12	0.01	ok
2	R-3405	2.34	3.95	0.75	0.50	2.59	0.34	0.41	ok
5	R-4215-C	1.10	5.65	1.65	0.75	6.99	0.16	0.02	ok

## **APPENDIX A: PRE-DEVELOPMENT RUNOFF DATA**

- **Sub-Basin Input Summary ..... A-1**
- **Time of Concentration – Pre-Developed Basin..... A-2**
- **2-yr – Pre-Development Basin Runoff Hydrograph and Results . A-3**
- **10-yr – Pre-Development Basin Runoff Hydrograph and Results A-4**

SUB-BASIN INPUT SUMMARY						
SN	Element ID	Description	Area (acres)	Drainage Node ID	Weighted Curve Number	Time of Concentration (days hh:mm:ss)
1	Post-Dev Basin		1.322	Stor-02	83.46	0 00:12:35
2	Pre-Dev Basin		1.316	Out-01	80.66	0 00:16:29

## TIME OF CONCENTRATION or TRAVEL TIME WORKSHEET

Project: Johnson County Training Center

Designer: BTV

Date: 8-Jun-23

Str. No.: Pre-Dev ToC

### Sheet Flow

1. Surface Description	grass	pavement	grass
2. Manning's Roughness Coeff., (n)	0.170	0.011	0.170
3. Flow Length, (L) **total L<= 300 ft	17.05 ft.	0.00 ft.	82.56 ft.
4. Two-yr 24-hr Rainfall, (P2)	2.93 in.	2.92 in.	2.92 in.
5. Land Slope, (s)	0.3300 ft./ft.	0.0200 ft./ft.	0.0100 ft./ft.
6. Travel Time, (Tt) (Tt = [0.007(nL)^0.8]/[P2^0.5*s^0.4])	0.015 hr	+	0.000 hr
			+
			0.214 hr

### Shallow Concentrated Flow

7. Surface Description (paved or unpaved)	unpaved	paved	unpaved
8. Flow Length, (L)	222.40 ft.	44.80 ft.	0.00 ft.
9. Watercourse Slope, (s)	0.0120 ft./ft.	0.0100 ft./ft.	0.0102 ft./ft.
10. Average Velocity, (V) (Vp = 20.3282(s)^0.5) (Vup = 16.1345(s)^0.5)	1.767 ft./s	1.613 ft./s	1.630 ft./s
11. Travel Time, (Tt) (Tt = L/3600V)	0.035 hr	+	0.008 hr
			+
			0.000 hr

Watershed or  
Subarea Tc or Tt =

0.271 hr

or


16.29 min

### Channel Flow

12. Cross Sectional Flow Area, (a)	0.32 ft.^2	7.07 ft.^2	20.20 ft.^2
13. Wetted Perimeter, Pw	1.68 ft.	4.71 ft.	18.20 ft.
14. Hydraulic Radius, (r) (r = a/Pw)	0.189 ft.	1.501 ft.	1.110 ft.
15. Channel Slope, (s)	0.0038 ft./ft.	0.0120 ft./ft.	0.0050 ft./ft.
16. Manning's Roughness Coeff., (n)	0.170	0.170	0.060
17. Velocity, (V) (V = [1.49*r^0.67*s^0.5]/n)	0.177 ft./s	1.260 ft./s	1.883 ft./s
18. Flow Length, (L)	0.00 ft.	0.00 ft.	0.00 ft.
19. Travel Time, (Tt) (Tt = L/3600V)	0.000 hr	+	0.000 hr
			+
			0.000 hr




## 2yr Pre-Development Basin Runoff Hydrograph and Results



Element ID	Pre-Dev Basin
Maximum Runoff (cfs)	<b>1.92</b>
Minimum Runoff (cfs)	0.00
Event Mean Runoff (cfs)	0.02
Duration of Exceedances (hrs)	N/A
Duration of Deficits (hrs)	N/A
Number of Exceedances	N/A
Number of Deficits	N/A
Volume of Exceedance (ft <sup>3</sup> )	N/A
Volume of Deficit (ft <sup>3</sup> )	N/A
Total Runoff (ft <sup>3</sup> )	5926.73
Detention Storage (ft <sup>3</sup> )	N/A
Exceedance	0
Deficit	0

## 10yr Pre-Development Basin Runoff Hydrograph and Results




Element ID	Pre-Dev Basin
Maximum Runoff (cfs)	<b>3.38</b>
Minimum Runoff (cfs)	0.00
Event Mean Runoff (cfs)	0.04
Duration of Exceedances (hrs)	N/A
Duration of Deficits (hrs)	N/A
Number of Exceedances	N/A
Number of Deficits	N/A
Volume of Exceedance (ft³)	N/A
Volume of Deficit (ft³)	N/A
Total Runoff (ft³)	10423.61
Detention Storage (ft³)	N/A
Exceedance	0
Deficit	0

## **APPENDIX B: POST-DEVELOPMENT RUNOFF AND WATER QUALITY CALCULATIONS DATA**


- **10-yr – Post-Development Basin Runoff Hydrograph and Results....B-1**
- **100-yr – Post-Development Basin Runoff Hydrograph and Results..B-2**

## 10yr Post-Development Basin Runoff Hydrograph and Results



Element ID	Post-Dev Basin
Maximum Runoff (cfs)	<b>4.15</b>
Minimum Runoff (cfs)	0.00
Event Mean Runoff (cfs)	0.04
Duration of Exceedances (hrs)	N/A
Duration of Deficits (hrs)	N/A
Number of Exceedances	N/A
Number of Deficits	N/A
Volume of Exceedance (ft³)	N/A
Volume of Deficit (ft³)	N/A
Total Runoff (ft³)	11602.88
Detention Storage (ft³)	N/A
Exceedance	0
Deficit	0

## 100yr Post-Development Basin Runoff Hydrograph and Results



Element ID	Post-Dev Basin
Maximum Runoff (cfs)	<b>6.92</b>
Minimum Runoff (cfs)	0.00
Event Mean Runoff (cfs)	0.08
Duration of Exceedances (hrs)	N/A
Duration of Deficits (hrs)	N/A
Number of Exceedances	N/A
Number of Deficits	N/A
Volume of Exceedance (ft³)	N/A
Volume of Deficit (ft³)	N/A
Total Runoff (ft³)	19603.67
Detention Storage (ft³)	N/A
Exceedance	0
Deficit	0

## **APPENDIX C: PROPOSED POND DATA**

■	Underground Detention Stage-Storage Spreadsheet .....	C-1
■	Storage Node Summary .....	C-2
■	Orifice Input Summary .....	C-3
■	Junction Input Summary .....	C-4
■	Pipe Input Summary .....	C-5
■	Outfall Input Summary .....	C-6
■	10-yr – Post-Developed Routed Flow Hydrograph and Results ...	C-7
■	100-yr – Post-Developed Routed Flow Hydrograph and Results .	C-8
■	10-yr – Post-Developed Proposed Pond Routed Elevation Hydrograph and Results.....	C-9
■	100-yr – Post-Developed Proposed Pond Routed Elevation Hydrograph and Results.....	C-10

Project: **Johnson County Training Center**



Chamber Model - MC-3500  
 Units - Imperial [Click Here for Metric](#)  
 Number of Chambers - 36  
 Number of End Caps - 12  
 Voids in the stone (porosity) - 40 %  
 Base of Stone Elevation - 725.20 ft  
 Amount of Stone Above Chambers - 12 in  
 Amount of Stone Below Chambers - 9 in  
 Amount of Stone Between Chambers - 6 in  
 Area of system - 2000 sf Min. Area - 1980 sf min. area

☒ Include Perimeter Stone in Calculations

### StormTech MC-3500 Cumulative Storage Volumes

Height of System (inches)	Incremental Single Chamber (cubic feet)	Incremental Single End Cap (cubic feet)	Incremental Chambers (cubic feet)	Incremental End Cap (cubic feet)	Incremental Stone (cubic feet)	Incremental Ch. EC and Stone (cubic feet)	Cumulative System (cubic feet)	Elevation (feet)
66	0.00	0.00	0.00	0.00	66.67	66.67	6882.54	730.70
65	0.00	0.00	0.00	0.00	66.67	66.67	6815.88	730.62
64	0.00	0.00	0.00	0.00	66.67	66.67	6749.21	730.53
63	0.00	0.00	0.00	0.00	66.67	66.67	6682.54	730.45
62	0.00	0.00	0.00	0.00	66.67	66.67	6615.88	730.37
61	0.00	0.00	0.00	0.00	66.67	66.67	6549.21	730.28
60	0.00	0.00	0.00	0.00	66.67	66.67	6482.54	730.20
59	0.00	0.00	0.00	0.00	66.67	66.67	6415.88	730.12
58	0.00	0.00	0.00	0.00	66.67	66.67	6349.21	730.03
57	0.00	0.00	0.00	0.00	66.67	66.67	6282.54	729.95
56	0.00	0.00	0.00	0.00	66.67	66.67	6215.88	729.87
55	0.00	0.00	0.00	0.00	66.67	66.67	6149.21	729.78
54	0.06	0.00	2.09	0.00	65.83	67.92	6082.54	729.70
53	0.19	0.02	6.99	0.29	63.76	71.03	6014.62	729.62
52	0.29	0.04	10.58	0.45	62.25	73.29	5943.59	729.53
51	0.40	0.05	14.53	0.62	60.61	75.76	5870.30	729.45
50	0.69	0.07	24.74	0.81	56.45	82.00	5794.55	729.37
49	1.03	0.09	37.02	1.06	51.44	89.51	5712.55	729.28
48	1.25	0.11	44.98	1.29	48.16	94.43	5623.04	729.20
47	1.42	0.13	51.20	1.52	45.58	98.30	5528.61	729.12
46	1.57	0.14	56.63	1.73	43.32	101.69	5430.31	729.03
45	1.71	0.16	61.46	1.95	41.30	104.71	5328.63	728.95
44	1.83	0.18	65.83	2.18	39.46	107.47	5223.91	728.87
43	1.94	0.20	69.76	2.41	37.80	109.97	5116.44	728.78
42	2.04	0.22	73.47	2.62	36.23	112.32	5006.48	728.70
41	2.13	0.23	76.85	2.82	34.80	114.47	4894.16	728.62
40	2.22	0.25	80.07	3.01	33.44	116.51	4779.69	728.53
39	2.31	0.27	83.04	3.19	32.17	118.41	4663.17	728.45
38	2.38	0.28	85.85	3.36	30.98	120.19	4544.77	728.37
37	2.46	0.29	88.53	3.53	29.84	121.90	4424.58	728.28
36	2.53	0.31	91.01	3.69	28.78	123.49	4302.68	728.20
35	2.59	0.32	93.37	3.85	27.78	125.00	4179.18	728.12
34	2.66	0.33	95.62	4.01	26.81	126.45	4054.18	728.03
33	2.72	0.35	97.74	4.16	25.90	127.81	3927.74	727.95
32	2.77	0.36	99.77	4.32	25.03	129.12	3799.92	727.87
31	2.82	0.37	101.69	4.47	24.20	130.36	3670.81	727.78
30	2.88	0.38	103.52	4.61	23.42	131.54	3540.45	727.70
29	2.92	0.40	105.27	4.75	22.66	132.68	3408.90	727.62
28	2.97	0.41	106.92	4.89	21.94	133.75	3276.22	727.53
27	3.01	0.42	108.45	5.02	21.28	134.75	3142.47	727.45
26	3.05	0.43	109.92	5.16	20.64	135.71	3007.72	727.37
25	3.09	0.44	111.39	5.28	20.00	136.67	2872.01	727.28
24	3.13	0.45	112.70	5.41	19.42	137.53	2735.34	727.20
23	3.17	0.46	113.96	5.53	18.87	138.36	2597.80	727.12
22	3.20	0.47	115.18	5.65	18.34	139.16	2459.44	727.03
21	3.23	0.48	116.32	5.76	17.83	139.92	2320.28	726.95
20	3.26	0.49	117.41	5.87	17.35	140.64	2180.36	726.87
19	3.29	0.50	118.45	5.98	16.90	141.32	2039.73	726.78
18	3.32	0.51	119.45	6.08	16.46	141.98	1898.41	726.70
17	3.34	0.51	120.39	6.17	16.04	142.60	1756.42	726.62
16	3.37	0.52	121.27	6.27	15.65	143.19	1613.82	726.53
15	3.39	0.53	122.13	6.35	15.27	143.76	1470.63	726.45
14	3.41	0.54	122.92	6.44	14.92	144.28	1326.87	726.37
13	3.44	0.54	123.73	6.52	14.57	144.82	1182.59	726.28
12	3.46	0.55	124.48	6.59	14.24	145.31	1037.77	726.20
11	3.48	0.56	125.23	6.66	13.91	145.80	892.46	726.12
10	3.51	0.59	126.18	7.14	13.34	146.66	746.66	726.03
9	0.00	0.00	0.00	0.00	66.67	66.67	600.00	725.95
8	0.00	0.00	0.00	0.00	66.67	66.67	533.33	725.87
7	0.00	0.00	0.00	0.00	66.67	66.67	466.67	725.78
6	0.00	0.00	0.00	0.00	66.67	66.67	400.00	725.70
5	0.00	0.00	0.00	0.00	66.67	66.67	333.33	725.62
4	0.00	0.00	0.00	0.00	66.67	66.67	266.67	725.53
3	0.00	0.00	0.00	0.00	66.67	66.67	200.00	725.45
2	0.00	0.00	0.00	0.00	66.67	66.67	133.33	725.37
1	0.00	0.00	0.00	0.00	66.67	66.67	66.67	725.28

Storage Node Input Summary Table											
SN	Element ID	X Coordinate	Y Coordinate	Description	Invert Elevation (ft)	Max (Rim) Elevation (ft)	Max (Rim) Offset (ft)	Initial Water Elevation (ft)	Initial Water Depth (ft)	Ponded Area (ft <sup>2</sup> )	Evaporation Loss
1	Stor-02	2123.91	3344.35		725.20	732.00	6.80	725.20	0.00	0.00	0.00




Orifice Input Summary Table															
SN	Element ID	Description	From (Inlet) Node	To (Outlet) Node	From (Inlet) Node Invert Elevation (ft)	To (Outlet) Node Invert Elevation (ft)	Orifice Type	Orifice Shape	Flap Gate	Circular Orifice Diameter (inches)	Rectangular Orifice Height (ft)	Rectangular Orifice Width (ft)	Orifice Invert Elevation (ft)	Orifice Invert Offset (ft)	Orifice Coefficient
1	100-YR Orifice		Stor-02	Outlet Structure	725.20	725.20	SIDE	RECT_CLOSED	NO		0.25	0.50	727.87	2.67	0.6260
2	10-YR Orifice		Stor-02	Outlet Structure	725.20	725.20	SIDE	CIRCULAR	NO	7.00			726.15	0.95	0.6140
3	WQ Orifice		Stor-02	Outlet Structure	725.20	725.20	SIDE	CIRCULAR	NO	2.00			725.20	0.00	0.6140

JUNCTION INPUT SUMMARY TABLE													
SN	Element ID	X Coordinate	Y Coordinate	Description	Invert Elevation (ft)	Ground/Rim (Max) Elevation (ft)	Ground/Rim (Max) Offset (ft)	Initial Water Elevation (ft)	Initial Water Depth (ft)	Surcharge Elevation (ft)	Surcharge Depth (ft)	Ponded Area (ft <sup>2</sup> )	Minimum Pipe Cover (inches)
1	Outlet Structure	3111.74	3353.33		725.20	734.50	9.30	725.20	0.00	0.00	734.50	0.00	0.00

PIPE INPUT SUMMARY TABLE																				
SN	Element ID	Description	From (Inlet) Node	To (Outlet) Node	Length (ft)	Inlet Invert Elevation (ft)	Inlet Invert Elevation Offset (ft)	Outlet Invert Elevation (ft)	Outlet Invert Offset (ft)	Total Drop (ft)	Average Slope (%)	Pipe Shape	Pipe Diameter or Height (inches)	Pipe Width (inches)	Manning's Roughness	Entrance Losses	Exit/Bend Losses	Additional Losses	Initial Flow (cfs)	Flap Gate
1	Outfall Pipe		Outlet Structure	Out-02	73.00	724.75	0.00	724.50	0.00	0.25	0.3400	CIRCULAR	24.000	0.00	0.0150	0.5000	0.5000	0.0000	0.00	NO


OUTFALL INPUT SUMMARY TABLE								
SN	Element ID	X Coordinate	Y Coordinate	Description	Invert Elevation (ft)	Boundary Type	Flap Gate	Fixed Water Elevation (ft)
1	Out-01	2258.43	6865.17		0.00	NORMAL	NO	
2	Out-02	3955.90	3362.31		724.50	NORMAL	NO	
3	Out-03	2999.66	478.62		0.00	NORMAL	NO	

## 10yr Post-Developed Routed Flow Hydrograph and Results




Element ID	Outlet Structure
Maximum Total Inflow (cfs)	<b>1.72</b>
Minimum Total Inflow (cfs)	0.00
Event Mean Total Inflow (cfs)	0.04
Duration of Exceedances (hrs)	N/A
Duration of Deficits (hrs)	N/A
Number of Exceedances	N/A
Number of Deficits	N/A
Volume of Exceedance (ft³)	N/A
Volume of Deficit (ft³)	N/A
Total Inflow Volume (ft³)	11596.66
Detention Storage (ft³)	N/A
Exceedance	0
Deficit	0

## 100yr Post-Developed Routed Flow Hydrograph and Results




Element ID	Outlet Structure
Maximum Total Inflow (cfs)	<b>3.37</b>
Minimum Total Inflow (cfs)	0.00
Event Mean Total Inflow (cfs)	0.08
Duration of Exceedances (hrs)	N/A
Duration of Deficits (hrs)	N/A
Number of Exceedances	N/A
Number of Deficits	N/A
Volume of Exceedance (ft³)	N/A
Volume of Deficit (ft³)	N/A
Total Inflow Volume (ft³)	19589.14
Detention Storage (ft³)	N/A
Exceedance	0
Deficit	0

## 10yr Post-Developed Pond Routed Elevation Hydrograph and Results



Element ID	Stor-02
Maximum Head (ft)	<b>727.86</b>
Minimum Head (ft)	725.20
Event Mean Head (ft)	726.24
Duration of Exceedances (hrs)	N/A
Duration of Deficits (hrs)	N/A
Number of Exceedances	N/A
Number of Deficits	N/A
Exceedance	0
Deficit	0

## 100yr Post-Developed Pond Routed Elevation Hydrograph and Results



Element ID	Stor-02
Maximum Head (ft)	<b>729.64</b>
Minimum Head (ft)	725.20
Event Mean Head (ft)	726.32
Duration of Exceedances (hrs)	N/A
Duration of Deficits (hrs)	N/A
Number of Exceedances	N/A
Number of Deficits	N/A
Exceedance	0
Deficit	0